

XTRAStop®550

SMOKE & DRAFT SEALANT



XtraStop®550 is designed for filling areas around wires, vents, pipes, ducts and other wall penetrations & construction voids. The product is a commercial quality, intumescent, non-combustible fire, smoke and draft prevention sealant. Water-based, it can be used wherever ASTM E-814 Specification is needed. The product is engineered to withstand 3000 degrees for up to 8 hours, and can be safely removed with soap and water prior to curing.

FEATURES

- Withstands 3000° F Exposures
- Bonds to Most Materials
- ASTM E-814 - 8 hours
- Non Combustible
- Water Resistant
- Non Toxic
- Non-Sag

APPLICATIONS

- Through wall penetrations
- Electrical service entrance
- Metallic & nonmetallic pipes/tubing
- Metal duct work
- Insulated pipes
- Masonry
- HVAC

Weather Defense System

This XtraBond® product is a part of the XtraGuard Weather Defense System™, an integrated product line of building components developed from advanced materials research that increase the durability and comfort of residential and commercial structures by effectively managing moisture. The product's aggressive adhesion and compatibility with all major building materials makes it a critical link in the XtraGuard Weather Defense System, when combined with the company's complete line of Wraps and Flashing Products.



Who is Premier?

This XtraBond® product is manufactured and distributed by Premier Building Solutions, a manufacturer of high performance systems that provide protection in commercial and residential buildings – as well as a variety of other industrial and transportation applications.

The company's history of innovation has led to the development of breakthrough adhesive chemistries and new industrial-strength products that help customers increase the efficiency and durability of their critical assets.





XTRAStop[®]550

SMOKE & DRAFT SEALANT



PROPERTIES:

ColorBrick Red
Curing Rate72 Hours @ 77 deg F/50% RH
Shrinkage+/- 5%
Application Temp40 degrees
ViscositySpreadable Paste
UV RatingNo discoloration or change in appearance

SPECIFICATIONS: XtraStop[®]550 meets or exceeds the requirements of ASTM E-814, ASTM E-119, ASTM-E136, ASTM-E84, ANSI A2.1, AFPA 25.1, UBC 43-1

COLOR: Brick Red

DIRECTIONS: For best results, prepare clean, dry surface. Contact surfaces should be free of oil and loose debris. Openings larger than one inch can be partially filled with mineral wool or, a suitable backing material to maximize yield. Apply with a caulking gun forcing sealant onto the substrate, then tool if needed (clean excess material with soap and water). It is the user's responsibility to thoroughly test the proposed use of our products with any and all substrates.

STORAGE: Material is to be stored under controlled dry environment (below 75° F). Use within 12 months from date of manufacture. For best results, keep material in tightly closed containers when not in use.

PACKAGING



CARTRIDGES



PAILS



55GAL DRUMS

LIMITED LIFETIME WARRANTY: This product is guaranteed to give satisfactory performance if applied in accordance with the label directions. Liability to Premier Building Solutions, Inc. (Premier) is limited to a full refund of the purchase price or product replacement if product is proven defective. Premier shall not be liable for loss or damage, whether direct, consequential or incidental. There are no other warranties expressed or implied including the implied warranty of merchantability or fitness for a particular purpose.

Premier Building Solutions specifically disclaims and makes no warranties, express or implied, about this product, its merchantability, or its fitness for a particular purpose. All recommendations, directions, and suggestions for its use are consistent with our testing and research for a variety of applications, but no promises, guarantees, or warranties are being made with regard to its use, whether or not consistent with the directions, or its effectiveness for any given application. Users of this product should do so in compliance with all applicable laws and regulations. User of this product should conduct its own field test, to assure results.

131120-PBS-XS550-Ver4